Revision Date 5/1/2020



Safety Data - Dixie Belle Mud: Black

1. Identification

Product identifier used on the label

Dixie Belle Paint Company - Dixie Belle Mud: Black

Company:

Dixie Belle Paint Co. 8019 Ridge Road Port Richey, FL 34668 Telephone: +1 813-909-1962

Emergency telephone number CHEMTREC: 1-800-424-9300

2. Hazard(s) Identification

Physical hazards Not classified.

Health hazards Carcinogenicity

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer by inhalation.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Category 1A

Response If exposed or concerned: Get medical advice/attention.

Disposal Dispose of in accordance with local, state, and federal regulations.

Hazard(s) not otherwise

classified (HNOC)

Not classified.

Revision Date 5/1/2020

3. Composition / Information on Ingredients

Chemical Name	CAS Number	%
Carbon Black	13333-86-4	0.04 - 0.07
Calcium Carbonate Mixture	471-34-1	0.5 – 0.65
Ethoxylated Surfactant	68154-97-2	0.02 – 0.07
Nonylphenol, Ethoxylated Surfactant	127087-87-0	0.07 – 0.12
Diacetone Alcohol	123-42-2	0.1 – 0.17
Additives	Proprietary	0.01

Mixtures

Chemical Name	CAS Number	%
Limestone	1317-65-3	> 60
Attapulgite	12174-11-7	< 20
Mica	12001-26-2	< 20
Starch	9005-25-8	< 5
Crystalline Silica (Quartz)	14808-60-7	< 1

Composition comments

All concentrations are in percent by weight unless ingredient is a gas.

Raw materials in this product contain respirable crystalline silica as an impurity. The weight percent of respirable crystalline silica found in this product is <1.0%. Exposures to respirable crystalline silica during the normal use of this product must be determined by workplace hygiene testing.

4. First-Aid Measures

Inhalation Dust irritates the respiratory system and may cause coughing and difficulties in breathing. Move

injured person into fresh air and keep person calm under observation. Get medical attention if

symptoms persist.

Skin contact Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or

persists.

Eye contact Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical

assistance.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Under normal conditions of intended use, this material does not pose a risk to health. Dust may

irritate throat and respiratory system and cause coughing.

Provide general supportive measures and treat symptomatically.

Indication of immediate medical attention and special

treatment needed

General information Ensure that medical personnel are aware of the material(s) involved.

Revision Date 5/1/2020

5. Fire-Fighting Measures

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media

Not applicable.

Specific hazards arising from

the chemical

Not a fire hazard.

Special protective equipment and precautions for firefighters

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in

case of fire.

Fire-fighting

Specific methods

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

Cool material exposed to heat with water spray and remove it if no risk is involved.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up

Vacuum up the spilled material. Vacuums used for this purpose should be equipped with HEPA filters. Collect in approved containers and seal securely. Containers must be labeled. For waste

disposal, see Section 13 of the SDS.

Environmental precautions Avoid discharge to drains, sewers, and other water systems.

7. Handling and Storage

Precautions for safe handling

Minimize dust production when mixing, sanding, or opening and closing bags. Avoid inhalation of dust. Wear appropriate personal protective equipment. Wash hands after handling. Observe good industrial hygiene practices and use appropriate lifting techniques.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated place. Store in a closed container away from incompatible materials. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a moldy appearance or an unpleasant odor. Keep containers closed when not in use.

8. Exposure Controls/Personal Protection

Exposure Guidelines

Chemical Name	ACHIH TLV	OSHA PEL	NIOSH IDLH
Carbon Black	TWA 3.0 mg/m ³	PEL 3.5 mg/m ³	TWA 3.5 mg/m ³
Calcium Carbonate	TWA 10mg/m ³	Data Not Available	Data Not Available
Ethoxylated Surfactant	Data Not Available	Data Not Available	Data Not Available
Nonylphenol, Ethoxylated Surfactant	Data Not Available	Data Not Available	Data Not Available
Diacetone Alcohol	TWA 50 ppm	PEL 50 ppm	Data Not Available

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Limestone (CAS 1317-65-3)	PEL	5 mg/m ³	Respirable Fraction Total Dust.
Starch (CAS 9005-25-8)	PEL	5 mg/m ³ 15 mg/m ³	Respirable Fraction. Total Dust.

Revision Date 5/1/2020

Components	туре	value
Mica (CAS 12001-26-2)	TWA	20 mppcf

1/-1---

Impurities	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.
,		0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Туре	Value	Form
Mica (CAS 12001-26-2)	TWA	3 mg/m3	Respirable fraction.
Starch (CAS 9005-25-8)	TWA	10 mg/m3	
Impurities	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

US NIOSH Pocket Guide to Chemical Hazards: Recommended exposure limit (REL)

Type

Components	Туре	Value	Form
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Mica (CAS 12001-26-2)	TWA	3 mg/m3	Respirable.
Starch (CAS 9005-25-8)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Impurities	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide sufficient ventilation for operations causing dust formation. Observe occupational exposure limits and minimize the risk of exposure.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved safety goggles.

Skin protection

Hand protection It is a good industrial hygiene practice to minimize skin contact. For prolonged or repeated skin

contact use suitable protective gloves.

Other Normal work clothing (long sleeved shirts and long pants) is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use.

Thermal hazards None.

General hygiene Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any

medical surveillance requirements.

Revision Date 5/1/2020

9. Physical and Chemical Properties

Appearance

Physical state: Solid. Form: Powder. Color: White to off-white.

Odor: Low to no odor. Odor threshold: Not applicable

7.5 - 9.9pН

Melting point/freezing point Not applicable. Initial boiling point and boiling Not applicable.

range

Flash point Not applicable. **Evaporation rate** Not applicable. Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits Not applicable.

Flammability limit lower

(%)

Not applicable.

Flammability limit - upper

Explosive limit - lower (%) Not applicable. Explosive limit - upper (%) Not applicable.

Vapor pressure Not applicable. Vapor density Not applicable. 1.4 - 1.8 (H2O=1) Relative density Solubility(ies) Soluble in water. Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperature Not applicable. **Decomposition temperature** Not applicable. **Viscosity** Not applicable. Other information 90 -112lbs/ft3

Bulk Density:

VOC (Weight%): None Detected.

10. Stability and Reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Exposure to moisture.

Incompatible materials None known.

Hazardous decomposition

Above 1472°F (800°C) limestone (CaCO3) can decompose to lime (CaO) and release carbon products

dioxide (CO2).

Revision Date 5/1/2020

11. Toxicological Information

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Carbon Black	> 8,000 mg/kg (rat)	Data Not Available	Data Not Available
Calcium Carbonate	LD50>6,450 mg/kg (rat)	Data Not Available	Data Not Available
Ethoxylated Surfactant	Data Not Available	Data Not Available	Data Not Available
Nonylphenol, Ethoxylated Surfactant	>3314 mg/kg (rat)	>3000 mg/kg (rabbit)	Data Not Available
Diacetone Alcohol	4 g/kg (rat)	14.5 ml/kg (rabbit)	Data Not Available

Information on likely routes of exposure

Ingestion May cause discomfort if swallowed.

Inhalation Inhalation of dusts may cause respiratory irritation. Prolonged and repeated exposure to airborne

respirable crystalline silica can cause silicosis and/or lung cancer.

Skin contact Under normal conditions of intended use, this material does not pose a skin hazard.

Eye contact Direct contact with airborne particulates may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system

causing sneezing and/or coughing.

Information on toxicological effects

Acute toxicity

Not expected to be a hazard under normal conditions of intended use.

Skin corrosion/irritation

Prolonged or repeated skin contact may cause drying, cracking, or irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

12. Ecological Information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data available.

Bioaccumulative potential Bioaccumulation is not expected.

Mobility in soil No data available.

Other adverse effects None expected.

13. Disposal Considerations

Disposal instructionsDispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.

Local disposal regulations Dispose of in accordance with local regulations.

Hazardous waste code Not regulated.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations.

Revision Date 5/1/2020

14. Transport Information

DOT

Not regulated as a hazardous material by DOT.

IATA

Not regulated as a dangerous good.

IMDG

Not regulated as a dangerous good.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory Information

US Federal Regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard: Yes
Delayed Hazard: Yes
Fire Hazard: No

Pressure Hazard: No Reactivity Hazard: No

SARA 302 Extremely Hazardous Substance: No

SARA 311/312 Hazardous Chemical: Yes SARA 313 (TRI Reporting): Not Regulated.

Other Federal Regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Not Regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Not Regulated

Safe Drinking Water Act

(SDWA)

Not regulated.

Food and Drug

Not regulated.

Administration (FDA)

US State Regulations

US. Massachusetts RTK - Substance List

Crystalline silica (Quartz) (CAS 14808-60-7) Limestone (CAS 1317-65-3) Mica (CAS 12001-26-2) Starch (CAS 9005-25-8)

US. New Jersey Worker and Community Right-to-Know Act

Not regulated.

Revision Date 5/1/2020

US. Pennsylvania RTK - Hazardous Substances

Crystalline silica (Quartz) (CAS 14808-60-7) Limestone (CAS 1317-65-3) Mica (CAS 12001-26-2) Starch (CAS 9005-25-8)

US. Rhode Island RTK Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Attapulgite (CAS 12174-11-7)

Crystalline silica (Quartz) (CAS 14808-60-7)

16. Other Information, Including Date of Preparation or Last Revision

Issue date 04-May-2020

Revision date - Version # 01

Further information Crystalline silica: Raw materials in this product may contain respirable crystalline silica.

Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis)

and/or lung cancer.

Attapulgite: Carcinogenic to experimental animals via a route of exposure not relevant to human

exposure. NFPA Ratings: Health: 1 Flammability: 0 Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA Ratings



List of abbreviations NFPA: National Fire Protection Association.

References Registry of Toxic Effects of Chemical Substances (RTECS)

HSDB® - Hazardous Substances Data Bank

Torben et al. (2001). Environmental and Health Assessment of Substances in Household

Detergents and Cosmetic Products.

Disclaimer This information is provided without warranty. The information is believed to be correct. This

information should be used to make an independent determination of the methods to safeguard

workers and the environment